

MASSIME POTENZE DISSIPABILI e CLASSI di TEMPERATURA in funzione della TEMPERATURA AMBIENTE

serie
S
SO
EMH90

B

CUSTODIA	MAX. TEMPERATURA AMBIENTE	MAX. POTENZA DISSIPABILE	CLASSE DI TEMPERATURA	MAX. TEMPERATURA SUPERFICIALE	TEMPERATURA INGRESSO CAVO	TIPO O-RING
S..4 S..4/.. SO..4 SO..4/..	40°C	7,5 W	T6	T85°C	80°C	EPDM / SILICONE
	50°C	5,5 W				
	60°C	3,0 W				
	70°C	1,0 W				
	40°C	11,0 W	T5	T100°C	95°C	EPDM / SILICONE
	50°C	8,5 W				
	60°C	6,0 W				
	70°C	4,5 W				
	85°C	1,0 W	T4	T135°C	130°C	SILICONE
	40°C	19,5 W				
	50°C	17,0 W				
	60°C	14,0 W				
70°C	12,0 W	T6	T85°C	80°C	EPDM / SILICONE	
85°C	8,5 W					
40°C	8,0 W					
50°C	5,5 W					
S..6 S..6/.. SO..6 SO..6/..	60°C	3,0 W	T5	T100°C	95°C	EPDM / SILICONE
	70°C	1,0 W				
	40°C	11,5 W				
	50°C	9,0 W				
	60°C	6,5 W	T4	T135°C	130°C	SILICONE
	70°C	4,5 W				
	85°C	1,0 W				
	40°C	20,5 W				
	50°C	18,0 W	T6	T85°C	80°C	EPDM / SILICONE
	60°C	15,0 W				
	70°C	12,5 W				
	85°C	9,0 W				
S..7 S..7/.. SO..7 SO..7/.. EMH 90	40°C	11,0 W	T5	T100°C	95°C	EPDM / SILICONE
	50°C	7,5 W				
	60°C	4,5 W				
	70°C	2,0 W				
	40°C	16,0 W	T4	T135°C	130°C	SILICONE
	50°C	12,5 W				
	60°C	9,0 W				
	70°C	6,0 W				
	85°C	2,0 W	T6	T85°C	80°C	EPDM / SILICONE
	40°C	31,0 W				
	50°C	27,0 W				
	60°C	22,0 W				
70°C	18,0 W	T5	T100°C	95°C	EPDM / SILICONE	
85°C	12,5 W					
40°C	14,0 W					
50°C	10,0 W					
S..9 S..9/.. SO..9 SO..9/..	60°C	6,0 W	T4	T135°C	130°C	SILICONE
	70°C	2,5 W				
	40°C	21,0 W				
	50°C	16,0 W				
	60°C	12,0 W	T5	T100°C	95°C	EPDM / SILICONE
	70°C	8,0 W				
	85°C	2,5 W				
	40°C	42,0 W				
	50°C	35,0 W	T6	T85°C	80°C	EPDM / SILICONE
	60°C	29,0 W				
	70°C	24,0 W				
	85°C	16,0 W				